

AT-2000Plus FEATURES:

- Multi-Handset Cordless Telephone
- Base Unit Hands-Free Dialing and Answer Function
- Base Unit Ring Volume On/Off
- Base Unit Voice Volume Adjustable
- Hold Music
- Tone/Pulse Dialing Mode Selectable
- Last Number Redial
- Conference Call
- Backlighting on Both Base and Handset Keypad
- 40-Channel Autoscan
- High Power Handset
- Longer Range
- Touch Any Key Answer Function for Handset
- 12-number Memory for each Handset (15 digits)
- Handset with Power Saving Circuit, 85-hrs Stand-By Time and 2-hrs In-Use Time for Handset
- Low Battery Indication For Handset
- Built-in Noise Cancellation Circuit (Compander)
- Handset Scramble Function
- Handset Twin Charger. Handset Charged by the Front Slot, and Back-Up Battery Charged by the Back Slot
- Hands-Free Headset (Optional)
- Manual Handset Channel Change Function If Interference Occurs During Outside Call Conversation

AT-2000 Plus BH PRODUCT SPECIFICATION

General Items	Base Unit	Handset Unit
Transmitter		
Output Power	1.2 W	650 mW
Frequency	382.100 MHz	256.100 MHz
Modulation Type	FM	FM
Spurious Emission	-60db	-50db
Current Consumption		
Stand-by	60mA	12mA
Talk	600mA	500mA
Receiver		
Frequency	256.100 MHz	382.100MHz
Sensitivity at 12db SINAD	-125dbm	-125dbm.
Audio Distortion	< 5%	< 5%
Image/Harmonic	-80db	-70db
Adjacent Channel Rejection	-70db	-70db
Spurious Response	-70db	-70db
Power Source	AC 110V/60Hz AC 220V/ 50Hz Output: DC 18V/800mA	DC 3.6V/1200mA Ni-Mh Battery
Handset Charger Power Source		Input: AC 110/220V Output: DC 9V/ 500mA
Dimension (L X W X H)	222X159X57 mm	156X50X31 mm
Weight	760g	220g
AT-2000 Plus BH Dimension Include Color Box	510X300X75 mm	
AT-2000 Plus BH Weight Include Color Box	2.5 kg	